



Technologie AG

VARIO 75 MOBILE





SPECIFICATIONS

Operable in multiple modes
HiPRESS- or HiCAFS- in Jet- or Spray-Mode



SPECS

VARIO 75 MOBILE

Filling Volume		75 litres (3 x 25 l or 1 x 75 L)
Pressure Vessel		3 x 25 l or 1 x 75 L Stainless Steel, Custom Colour
Framing		Made of Aluminium, Powder Coated
Hose		15 m up to 30 m EN-854
Hose Reel		Automatic or Manual Rewind
Fire Rating		A, IV B
Suitable for electrical devices		Up to 1000 V / Distance 2 m
Suitable for		Any Liquid Fire Agent premix or extinguishing agent cartridge
Propellant		Compressed Air Bottle - 9 l Carbon Composite / 300 bar
Working Pressure		28 bar
Operation Time	(HiPRESS HiCAFS Spray)	app. 114 s 158 s 383 s
Throwing Distance	(HiPRESS HiCAFS Spray)	app. 19 m 17,5 m 8-10 m
Throughput	(HiPRESS HiCAFS Spray)	39,5 l/min 28,5 l/min 11,5 l/min
Temperature Range		-25°C to 60°C
Weight empty front hose module; back tank module:		app. 26 kg; app. 83 kg